



PRODUCT CODE **16SS**

**DRUMSAVER™ INSERT FOR STEEL DRUMS**

**PRODUCT DESCRIPTION:** The 16SS is a straight-sided, seamless, vacuum-formed insert for 16-gallon open-head steel drums. It is molded from FDA-approved low-density polyethylene. A contoured lip snaps over the top bead to prevent leakage between the insert and the drum wall, while also providing easy drum closure using a standard ring and bolt or lock assembly.

**Insert Specifications**

**MATERIAL USED**

Low-density polyethylene

**INSERT DIMENSIONS**

Diameter: 14.0" (+0.25"/-0")

Height: 25.5" (+/-0.125")

Average thickness: 15 mil (+/-10%)

**WEIGHT**

10 oz. (+/-10%)

**SIDE-WALL DESIGN**

Straight-sided

**TEMPERATURE PARAMETERS**

High (momentary): 175° (195°)F

Low: -40°F

**Packaging Specifications**

**CARTON WEIGHT**

40 lb.

**CARTON DIMENSIONS**

Length: 29.5"

Width: 22"

Height: 18"

**QUANTITY/CASE**

50

**PACKAGING STYLE**

Flat-pack

**TYPICAL APPLICATIONS:** The 16SS is ideal for drums using follower plates, or users who prefer a straight-sided insert. It is perfect for mixing, pumping and storing all liquids, powders and pastes that can be contained in low-density polyethylene. Examples include chemicals, inks, adhesives, greases, paints, coatings, silicones, and food. Can be used when rolling drums.

All statements, technical information and recommendations contained herein are based on tests CDF believes to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following warranty is made in lieu of all other warranties, expressed or implied. CDF warrants its products will be free from defects in material and workmanship upon delivery. CDF's sole obligation and liability shall be to replace products that are defective provided the defective products are returned to CDF. The foregoing limited warranty is exclusive and expressly in lieu of all other warranties (express or implied including but not limited to the warranties of merchantability and fitness for a particular purpose), liabilities, or claims or remedies in contract, tort or otherwise. Neither CDF nor its suppliers shall be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the products. Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith.

CDF CORPORATION • 77 Industrial Park Road • Plymouth, MA 02360  
(800) 443-1920 • fax (508) 747-6333 • www.cdf1.com

Specifications subject to change without notice.  
Product Specification: 16SS  
Revision: E  
10.2.08