## Aseptic Liners

CDF's high-capacity aseptic liners provide outstanding performance in critical food applications, such as high and low acid products, tomato, fruit juice and any other food product requiring aseptic packaging.



### **Benefits**

- Strong oxygen barrier greatly extends shelf life for foods
- Ensures the absolute purity of your product
- Can accommodate 1", 2" and 3" fillers with capacities up to 330 gallon intermediate bulk size
- Using specialized barrier films, high-capacity aseptic bags lock out light
- Can accommodate high-speed fills
- Convenient design minimizes bag handling during a fill
- Fitments are available for most major aseptic fillers
- CDF offers a variety of films, fitments and fitment placements



# Aseptic Liners

## **Multiple Sizes**

Pillow-shaped industrial tote liners are available in the following sizes:

- 37.5" x 61" 55 gallons aseptic
- 81" x 81" 275 gallons aseptic, recommended for a standard wood bin tote or plastic IBC tote
- 81" x 85" 300 gallons aseptic, recommended for a standard wood bin tote or plastic IBC tote

## **Multiple Fitment Choices**

1", 2" and 3" fitments are available.

### **Material Choices**

All liners are made in America. The inside layer is made from FDA-approved films.

**EVOH** film is widely used in the food packaging industry. It is a strong, flexible, transparent film with good moisture and excellent oxygen barrier specifications.

**Barria<sup>™</sup>** metallized polyester provides an oxygen and water vapor barrier.

**Flexus™** and **Flexus HF** metallocene LLDPE are for general use and provide durability and flex crack resistance.

The film materials used in the manufacture of our IBC liners comply with FDA Regulations 21 CFR 177.1520, CFR 175.105, 177.1390 and CFR 177.1630.

We guarantee that our liners will be constructed from the specified materials and that CDF will not knowingly use materials that are out of specification or could be adulterated. No additives are introduced during the heat-sealing process.

### **Custom Designs**

CDF will always consider custom designs.



CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.** 

CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

For more information or to request a free sample, please call **1-800-443-1920** or visit **www.cdf1.com** today! CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2014 CDF Corporation | 0414A

