

DrumSaver™

Steel Drum Liners

DrumSaver steel drum liners are designed for steel drums. The seamless vacuum-formed drum liners have a contoured lip that snaps over an open-head drum's top bead, preventing leakage between the drum liner and drum wall and providing easy drum closure using a standard ring and bolt or lock assembly. DrumSaver liners are

perfect for mixing, pumping and storing nearly any liquid, powder or paste. Examples include chemicals, inks, adhesives, greases, paints, coatings, silicones and food.



Benefits

- Ensures the absolute purity of your product
- Provides protection against drum corrosion
- Environment-friendly packaging, helps users to reach sustainability goals
- Reduces drum cleaning and reconditioning costs



DrumSaver™

Steel Drum Liners

Available in 4 designs:

Straight-sided inserts fit smoothly into new drums and are ideal when using follower plates.

Accordion inserts have flexible, pleated, side walls that accommodate variations in reconditioned drum heights.

Combination inserts combine a straight-sided design with a band of accordion pleats to accommodate both drum height variations and follower-plate use.

Vented inserts include four holes near the top to vent trapped air during a fill, allowing drums to be filled with the lid on.

Multiple Sizes

DrumSaver liners are available in straight-sided for 12, 16, 30 and 55 gallon drums, accordion for 55 gallon drums and combination for 55 gallon drums.

Material Choices

All liners are made in America from FDA-approved films.

Low-density polyethylene is intended for general use and provides superb tensile strength and elongation, as well as high resistance to tears and flex cracking. Low-density polyethylene is designed for applications up to 175°F.

Polypropylene is designed for hot-fill applications up to 270°F.

Anti-stat LDPE contains an internal anti-stat agent to aid in the reduction of static build-up, thus reducing dry chemical static cling and chance of ignition of flammable materials.

Custom Designs

CDF will always consider custom designs.

Most Popular Products

- 16SS
- 3015
- 55
- 5515/34.00-G4/VTD
- 5515/34.25-G4



CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.**

CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

For more information or to request a free sample, please call **1-800-443-1920** or visit **www.cdf1.com** today!

CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2014 CDF Corporation | 0414A

