



PRODUCT CODE **55/VTD**

DRUMSAVER™ INSERT FOR STEEL DRUMS

PRODUCT DESCRIPTION: The 55/VTD, the vented version of the popular 55 insert, is an accordion-style, seamless, vacuum-formed insert for 55-gallon open-head steel drums. Flexible accordion-pleat side-walls accommodate variations in drum heights, a common issue with reconditioned drums. The 55/VTD is molded from FDA-approved low-density polyethylene and includes four 3/8" holes near the top to allow trapped air to escape from between the drum and the liner during fill. A contoured lip snaps over the top bead to prevent leakage between the insert and the drum wall, while also providing easy drum closure using a standard ring and bolt or lock assembly.

Insert Specifications

MATERIAL USED
Low-density polyethylene

INSERT DIMENSIONS
Diameter: 22.5" (+0.25"/-0")
Height: 33" - 34.5"
Average thickness: 15 mil (+/-10%)

WEIGHT
21 oz. (+/-10%)

SIDE-WALL DESIGN
Accordion

TEMPERATURE PARAMETERS
High (momentary): 175° (195°)F
Low: -40°F

Packaging Specifications

CARTON WEIGHT
29 lb.

CARTON DIMENSIONS
Length: 35"
Width: 21"
Height: 15"

QUANTITY/CASE
20

PACKAGING STYLE
Rolled

TYPICAL APPLICATIONS: The 55/VTD is designed for reconditioned drums because the accordion-style side wall design allows for a range of drum heights. The 55/VTD is perfect for filling with the lid on, heavy-duty mixing, pumping and storing all liquids, powders and pastes that can be contained in low-density polyethylene. Examples include chemicals, inks, adhesives, greases, paints, coatings, silicones, and food. Not recommended for drum rolling.

. CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith.** CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

**CDF CORPORATION • 77 Industrial Park Road • Plymouth, MA 02360
(800) 443-1920 • fax (508) 747-6333 • www.cdf1.com**

Specifications subject to change without notice.
Product Specification: 55/VTD
Revision: G
2.2.11