



PRODUCT CODE **CL55(#)**

LINERPRO™ CONDUCTIVE DRUM LINER

PRODUCT DESCRIPTION: This flat-seam, 55-gallon liner is electrically conductive and is designed to meet MIL-B-82647 and NFPA 56A specifications. The liner is designed for easy installation, and can be simply twisted and tied off to protect contents. Its flexible, heat-sealed construction is uniformly liquid tight.

Liner Specifications

MATERIAL USED

Low-density polyethylene

LINER DIMENSIONS

Diameter: 23.75" (+0.25"/0")

Lay-flat: 38"

Height: 60" (+0"/-2")

Average thickness: 4 mil (+/-10%)

WEIGHT

12.5 oz. (+/-10%)

TEMPERATURE PARAMETERS

High: 175° F

Low: -20° F

PROPERTIES

Surface resistivity: $10^3 - 10^5 \Omega/\text{sq.}$

Volume resistivity: $<3000 \Omega\text{-cm}$

Packaging Specifications

CARTON WEIGHT

71 lb.

CARTON DIMENSIONS

Length: 36"

Width: 27.25"

Height: 4.75"

QUANTITY/CASE

100

PACKAGING STYLE

Folded

CDF's CONDUCTIVE LINERS ARE MADE OF CONDUCTIVE LDPE, THAT IS INTENDED AS AN AID TO DISSIPATE STATIC BUILD-UP WHEN LINER AND DRUM ARE GROUNDED. THEY ARE NOT DESIGNED AS, AND SHOULD NOT BE USED AS, THE PRIMARY CONTROLLER OF STATIC ELECTRICITY IN A PROCESS. CDF RECOMMENDS THAT THE CUSTOMER SHOULD VERIFY RESISTIVITY AND FITNESS FOR USE. PLEASE CONSULT YOUR SAFETY ENGINEER, SAFETY CONSULTANT, OR CDF IF THERE IS ANY QUESTION AS TO APPROPRIATENESS OF USE.

TYPICAL APPLICATIONS: Conductive drum liners can be used for shipping or storing nearly any wet or dry product, viscous or thin liquid, powder, particulate or paste. They are recommended for use with flammable materials, including coatings, paints, adhesives, solvents or other materials that could cause friction and therefore static charge build-up. The film is resistant to weak acids, methanol, ethanol and isopropanol, and will significantly slow the attack of weak alkalines and ketones.

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith.** CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

CDF CORPORATION • 77 Industrial Park Road • Plymouth, MA 02360
(800) 443-1920 • fax (508) 747-6333 • www.cdf1.com

Specifications subject to change without notice.
Product Specification: CL55(#)
Revision: I
2.8.11