

55 Gallon Pillow Liner



When filled, these industrial tote liners form the shape of a pillow. Pillow-shaped liners are typically constructed with two or three plies of linear low-density polyethylene (LLDPE) and a barrier film when used for aseptic and oxygen-barrier applications. The 55 gallon pillow style liner with a 2" fill fitment works for all types of 55 gallon drums.

Applications

- Food & Beverage (concentrated fruit, edible oils, fish oil, fructose, jams, liquid egg and variegates such as caramel, marshmallow and fudge)
- Cosmetic (creams, lotions, pre-weigh)
- Pharmaceutical (creams)

Benefits

- Manufactured in a clean environment, using cutting-edge CDF1 Smart Seal Technology™ that monitors and ensures consistent, high quality seals
- Pillow-shaped liners ensure the absolute purity of your product
- Pillow-shaped liners provide versatility; the same size bag fits many container sizes



55 Gallon Pillow Liner

CDF1 Smart Seal Technology™

Using state-of-the-art equipment and quality control standards of the highest caliber, CDF1 Smart Seal Technology ensures the ultimate reliability of IBC pillow liners. Proprietary CDF1 Smart Seal Technology optimizes precision and consistency through monitoring the temperature, time and pressure of every seal on every liner.

Multiple Sizes

Pillow liners are available in a number of sizes from 55 gallons and up. Please contact Customer Service for more details.

Multiple Fitment Choices

CDF fitments are available in a variety of sizes.

Material Choices

All liners are made in America. The inside layer is made from FDA-approved films.

Barria™ metallized polyester is for oxygen and water vapor barrier.

Flexus™ and **Flexus HF** metallocene LLDPE are for general use, durability and flex crack resistance.

Tenalon™ co-extruded nylon film is for abrasion resistance, durability and strength.

The film materials used in the manufacture of our IBC liners comply with FDA Regulations 21 CFR 177.1520, CFR 175.105, CFR 177.1390 and CFR 177.1630.

We guarantee that our liners will be constructed from the specified materials and that CDF will not knowingly use materials that are out of specification or could be adulterated. No additives are introduced during the heat-sealing process.

Custom Designs

CDF will always consider custom designs.

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith. CDF products are intended for single use application. Any reuse of the liner and/or fitment voids this warranty.**

CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

For more information or to request a free sample, please call **1-800-443-1920** or visit **www.cdf1.com** today!

CDF Corporation, 77 Industrial Park Road, Plymouth, MA 02360 | ©2015 CDF Corporation | 1015A

